



Elektrischer Anschluss		
	3x220V-Variante:	3x400V-Variante:
V	3/PE/200-240	3/N/PE/380-41
Hz	50-60	
kW	9,75	
A	32,0	25,0
Netzseitige Absicherung		
Druckluftanschluss	6 bar - Schlauchtülle di = 6 mm	
Sattdampfleistung	11,7 kg/h	
Zulässiger Betriebsüberdruck	5-6 bar	
Kesselvolumen	6,5 l	
Wasserinhalt (NW)	3,0 l	
Wasseranschluss	R1/2"	
Maße und Gewicht		
Höhe	700 mm	
Breite	920 mm	
Tiefe	800 mm	
Gewicht	190 kg	
Schalldruckpegel: (gemessen in 1 m Abstand und 1,6 m Höhe)	Dämpfen:	85 dB (A)
	Blasen:	75 dB (A)

Electrical connection		
	3x220V-Version:	3x400V-Version:
V	3/PE/200-240	3/N/PE/380-41
Hz	50-60	
kW	9,75	
A	32,0	25,0
<i>Fuse protection</i>		
<i>Compressed air connection</i>		
	6 bar - hose nozzle diameter inside 6 mm	
<i>Capacity of saturated steam</i>		
	11,7 kg/h	
<i>Admissible operating overpressure</i>		
	5-6 bar	
<i>Boiler volume</i>		
	6,5 l	
<i>Water contents (min. water level)</i>		
	3,0 l	
<i>Water connection</i>		
	R1/2"	
Dimensions and weight		
<i>Height</i>		
	700 mm / 27.6 inch	
<i>Width</i>		
	920 mm / 36 inch	
<i>Depth</i>		
	800 mm / 31.5 inch	
<i>Weight</i>		
	190 kg / 418.5 lbs	
<i>Sound intensity level: (height 1.6 m, 1 m from the front edge)</i>		
	Steaming:	85 dB (A)
	Blowing:	75 dB (A)